

LED LIGHTING SOLUTION FOR COMMERCIAL INDOOR AND GREENHOUSE APPLICATIONS HM150 Series HM150-EXT-BAR Extend your canopy and increase your yield with HM150 extension bars. Easy to install on HM660 or HM960. Select your desired spacing, hang the driver on the light frame, and plug each side into the extra ports on the driver housing. HM150 will dim accordingly with your HM660/HM960.

FEATURES & BENEFITS

- Compatible with GrowPros Solutions HM660 or HM960
- Extension bars on each side add 1' x 4' to your canopy
- Easy to install and connect to HM660 or HM960
- · Multiple spacing configurations
- Sold as a pair


TECHNICAL	SPECIFICATIONS

WATTAGE	150W (each bar)		
INPUT POWER	120V-277V		
FREQUENCY	50/60Hz		
CONTROL	intergrated with HM660 + HM960		
POWER FACTOR	0.9		
THD	20%		
WORKING TEMPERATURE	-40°F ~ 122°F		
IP RATING	IP44, Suitable for dry & damp locations		
WARRANTY	7 year limited		
PERFORMANCE DATA	MAX. POWER		
PPF	368 µmol/s		
PPE	2.7 μmol/J		
HEAT LOAD			
HEAT LOAD PER PAIR	1,025 BTU		

MAXIMUM POWER ELECTRICAL DATA (each bar)

AC VOLTAGE	120V	208V	240V	277V
AC CURRENT	1.25A	.72A	.625A	.54A
AC POWER	150W	150W	150W	150W

SPECTRAL DISTRIBUTION



DIMENSIONS

